



**Bearing No. 7006DF**

D	55 mm
a	5.8 mm
C	13 mm
B	13 mm
d	30 mm
r1	0.6 mm
2B	26 mm
Width	13 mm
r min.	1 mm
Weight	0.135 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	35 mm
Da max.	52 mm
ra (max)	1 mm
da1 (min)	35 mm
Bore Size	30 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	30x55x13
da2 (min)	35 mm
Da2 (max)	52 mm
Da1 (max)	50 mm
Width (mm)	13
Configuration	Duplex
Bearing number	7006DF
Angle (?)	30 °
Outside Diameter	55 mm
Static Load Rating	20,300 N

Bore Diameter (mm)	30
Dynamic Load Rating	23,600 N
Outer Diameter (mm)	55
Limiting Speed - Oil	11,000 rpm
Fillet Radius/Chamfer	1 mm
Limiting Speed - Grease	8,500 rpm
(Grease) Lubrication Speed	8500 r/min
Basic dynamic load rating (C)	23,6 kN
Basic static load rating (C0)	20,3 kN