



Bearing No. 6015ZZ

D	115 mm
d	75 mm
B	20 mm
C	20 mm
rn	0,5 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
UNSPSC	31171504
da max	85,5 mm
Weight	0,649 Kg
r min.	1,1 mm
da min.	81,5 mm
Da max.	108,5 mm
ra max.	1 mm
series:	60
Category	Single Row Ball Bearing
Size (mm)	75x115x20
Enclosure	2 Metal Shields
Inventory	0.0
Snap Ring	No
bore type:	Round
Width (mm)	20
Weight / LBS	0.64
maximum rpm:	6700 RPM
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6015ZZ
bore diameter:	75 mm
overall width:	20 mm
cage material:	Steel
fillet radius:	1.1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.528 Inch 115 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	20 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	20 mm
outside diameter:	115 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	75
Outer Diameter (mm)	115
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	5700 rpm
static load capacity:	33500 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	33500 N
Internal Special Features	No
(Grease) Lubrication Speed	5 700 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	33,5 kN
Basic dynamic load rating (C)	39,5 kN
Maximum Capacity / Filling Slot	No