

**Bearing No. 23092-B-K-MB + AHX3092G-H**

l	202 mm
e	0,24
D	680 mm
B	163 mm
a	11 mm
b	37 mm
m	204 kg / Weight
d	460 mm
Size (mm)	440x680x163
Width (mm)	163
d <sub>s</sub>	12,5 mm
C <sub>r</sub>	3650000 N / Dynamic load rating (radial)
n <sub>s</sub>	23,5 mm
D <sub>1</sub>	612,2 mm
Y <sub>1</sub>	2,84
Y <sub>2</sub>	4,23
Y <sub>0</sub>	2,78
n <sub>G</sub>	970 1/min / Limiting speed
n <sub>B</sub>	580 1/min / Reference speed
m <sub>1</sub>	32,9 kg / Weight, withdrawal sleeve
C <sub>0r</sub>	7650000 N / Static load rating (radial)
Bearing number	23092-B-K-MB + AHX3092G-H
d <sub>1H</sub>	440 mm
d <sub>2G</sub>	Tr480X5

$C_{ur}$	440000 N / Fatigue limit load, radial
$r_{min}$	6 mm
$r_{a\ max}$	5 mm
$d_{a\ min}$	483 mm
$D_{a\ max}$	657 mm
Bore Diameter (mm)	440
Outer Diameter (mm)	680
- AHX3092G-H / Designation, withdrawal sleeve	AHX3092GH / Designation, withdrawal sleeve