



Bearing No. 6015ZZE

D	115 mm
d	75 mm
B	20 mm
C	20 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Width	20 mm
UNSPSC	31171504
r min.	1.1 mm
Weight	0.645 Kg
da min.	81 mm
Da max.	109 mm
ra max.	1.0 mm
Category	Single Row Ball Bearing
ra (max)	1 mm
Da (max)	109 mm
da (min)	81 mm
Factor fo	15.7
Inventory	0.0
Bore Size	75 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	75x115x20
Width (mm)	20
Configuration	Single Row
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric

Other Features	Deep Groove
Keyword String	Ball
Bearing number	6015ZZE
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.nachiamerica.com
Outer Race Width	0.787 Inch 20 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.528 Inch 115 Millimeter
Radial Clearance	0.010 to 0.030 mm
Weight / Kilogram	0
Manufacturer Name	NACHI
Bore Diameter (mm)	75
Internal Clearance	C0-Medium
Static Load Rating	33,500 N
Dynamic Load Rating	39,500 N
Outer Diameter (mm)	115
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	1.1 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	5,700 rpm
Internal Special Features	No

Basic dynamic load rating (C)	39,5 kN
Basic static load rating (C0)	33,5 kN
Maximum Capacity / Filling Slot	No