



Bearing No. 6015ZZNR

D	115,000 mm
d	75,000 mm
B	20,000 mm
C	20,000 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Size (mm)	75x115x20
Snap Ring	Yes
Inventory	0.0
Enclosure	2 Metal Shields
bore type:	Round
Width (mm)	20,000
Weight / LBS	0.64
Product Group	B00308
closure type:	Double Shielded
Cage Material	Steel
Inch - Metric	Metric
overall width:	20 mm
bore diameter:	75 mm
cage material:	Steel
Keyword String	Ball
fillet radius:	1.1 mm
Bearing number	6015ZZNR
Other Features	Deep Groove With Snap Ring Shell Alvania Prelubricated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0

finish/coating:	Uncoated
Long Description	75MM Bore; 115MM Outside Diameter; 20MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	0.787 Inch 20 Millimeter
Outside Diameter	4.528 Inch 115 Millimeter
Inner Race Width	0 Inch 0 Millimeter
outer ring width:	20 mm
inner ring width:	20 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0
precision rating:	ISO Class 0
outside diameter:	115 mm
Bore Diameter (mm)	75,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	115,000
snap ring included:	With Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	5700 rpm
static load capacity:	33500 N
Harmonized Tariff Code	8482.10.50.68

dynamic load capacity:	33500 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No