




Bearing No. 6016

D	125 mm
d	80 mm
B	22 mm
C	22 mm
r	1.1
Z_	14
B_	22
fo	15.6
D_	125
C0	40
ra	1
D_a	118.5
DE_	115.994
DI_	89.006
DA_	13.494
SRI	6.98
SRE	6.98
SRIX	0.025
Noun	Bearing
SRIN	-0.025
SREX	0.025
SREN	-0.025
Bore	3.15 Inch 80 Millimeter
mass	0.872
bomp	0
yobi	6016
SBRG	10
SDM_	102.5
KBRG	6101
Weight	0,872 Kg

UNSPSC	31171504
r min.	1,1 mm
LangID	1
da max	91 mm
ALPHA_	0
C_conv	47500
da min	86.5
Oil rpm	6300
ra max.	1 mm
Da max.	118,5 mm
da min.	86,5 mm
hidYobi	6016
GRS rpm	5300
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	80x125x22
Enclosure	Open
Inventory	0.0
Snap Ring	No
Prod_Type3	DGBB_SR_OT
Width (mm)	22
Weight / LBS	1.896
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6016
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	4.921 Inch 125 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter

Long Description	80MM Bore; 125MM Outside Diameter; 22MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.898
Internal Clearance	C0-Medium
Bore Diameter (mm)	80
Outer Diameter (mm)	125
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	6 300 r/min
Internal Special Features	No
(Grease) Lubrication Speed	5 300 r/min
Basic static load rating (C0)	40 kN
Basic dynamic load rating (C)	47,5 kN
Maximum Capacity / Filling Slot	No