



Bearing No. 23180-2CS5/VT143

| | |
|-----------------------------|------------------|
| b | 22.3 mm |
| K | 12 mm |
| d | 400 mm |
| D | 650 mm |
| B | 200 mm |
| Size (mm) | 650x400x200 |
| Width (mm) | 200 |
| Mass bearing | 255 kg |
| d ₂ | 458 mm |
| D ₁ | 587 mm |
| Bearing number | 23180-2CS5/VT143 |
| Limiting speed | 150 r/min |
| Bore Diameter (mm) | 650 |
| r _a max. | 5 mm |
| D _a max. | 624 mm |
| d _a max. | 458 mm |
| d _a min. | 426 mm |
| Outer Diameter (mm) | 400 |
| D _a - max. | 624 mm |
| Calculation factor e | 0.28 |
| d _a - min. | 426 mm |
| d _a - max. | 458 mm |
| r _a - max. | 5 mm |
| r _{1,2} min. | 6 mm |
| D ₁ ? | 587 mm |
| d ₂ ? | 458 mm |
| r _{1,2} - min. | 6 mm |
| Calculation factor - e | 0.28 |
| Basic dynamic load rating C | 4864 kN |

| | |
|----------------------------------|---------|
| Basic dynamic load rating - C | 4864 kN |
| Fatigue load limit P_u | 530 kN |
| Calculation factor Y_1 | 2.4 |
| Calculation factor Y_2 | 3.6 |
| Calculation factor Y_0 | 2.5 |
| Calculation factor - Y_0 | 2.5 |
| Calculation factor - Y_2 | 3.6 |
| Fatigue load limit - P_u | 530 kN |
| Calculation factor - Y_1 | 2.4 |
| Basic static load rating C_0 | 7650 kN |
| Basic static load rating - C_0 | 7650 kN |