



**Bearing No. NTA-512**

H	19.84
d	7,92 mm
D	19,05 mm
T	1,984 mm
Cu	1.05
Dc	19.05
d1	19.05
Dw	1.984
Eb	10,16 mm
Ca	5.83
Ea	16,256 mm
C0a	13.17
Dc1	7.92
Noun	Roller Assembly
UNSPSC	31171500
Bore 1	0.313 Inch   7.95 Millimeter
Banded	No
Bore 2	0.313 Inch   7.95 Millimeter
Height	0.078 Inch   1.981 Millimeter
h(max)	0.81
h(min)	0.76
S(max)	7.92
Weight	0,002 Kg
S(min)	7.85
Category	Thrust Roller Bearings
Inventory	22.0
Size (mm)	7.92x19.05x1.984
Width (mm)	1,984

Bearing No.	NTA-512
Weight / LBS	0.004
Product Group	B04144
Self Aligning	No
Cage Material	Steel
Inch - Metric	Inch
Bearing number	NTA-512
Keyword String	Thrust Needle
Other Features	Single Row   Two Piece Cage
Thrust Bearing	Yes
Rolling Element	Needle Roller Bearing
Precision Class	ABEC 1   ISO P0
Outside Diameter	0.75 Inch   19.05 Millimeter
Long Description	5/16" Bore 1; 5/16" Bore 2; 3/4" Outside Diameter; 5/64" Height; Needle Roller Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1   ISO P0; Roller Assembl
(Refer.)Mass(kg)	0.002
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Weight / Kilogram	0.002
Manufacturer Name	KOYO
Washer designation	TRA-512
Bore Diameter (mm)	7,92
Outer Diameter (mm)	19,05
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Only
Limiting speeds(min-1)	24000
Harmonized Tariff Code	8482.99.25.40

(Refer.)Washer mass(kg)	0.001
Manufacturer Item Number	NTA-512
Single or Double Direction	Single Direction
Basic static load rating (C0)	13,17 kN
Basic dynamic load rating (C)	5,83 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter