



Bearing No. NTA-613

H	21.44
d	9,53 mm
D	20,625 mm
T	1,984 mm
Cu	1.40
Dc	20.625
d1	20.62
Dw	1.984
Eb	11,68 mm
Ca	6.05
Ea	18,034 mm
C0a	14.32
Dc1	9.53
Noun	Roller Assembly
UNSPSC	31171500
Height	0.078 Inch 1.981 Millimeter
Banded	No
Bore 1	0.375 Inch 9.525 Millimeter
Bore 2	0.375 Inch 9.525 Millimeter
h(max)	0.81
h(min)	0.76
S(max)	9.53
Weight	0,002 Kg
S(min)	9.45
Category	Thrust Roller Bearings
Inventory	123.0
Size (mm)	9.53x20.625x1.984
Width (mm)	1,984

Bearing No.	NTA-613
Weight / LBS	0.004
Product Group	B04144
Self Aligning	No
Cage Material	Steel
Inch - Metric	Inch
Bearing number	NTA-613
Keyword String	Thrust Needle
Other Features	Single Row Two Piece Cage
Thrust Bearing	Yes
Rolling Element	Needle Roller Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	0.813 Inch 20.65 Millimeter
Long Description	3/8" Bore 1; 3/8" Bore 2; 13/16" Outside Diameter; 5/64" Height; Needle Roller Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1 ISO P0; Roller Assembl
(Refer.)Mass(kg)	0.002
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.002
Manufacturer Name	KOYO
Bore Diameter (mm)	9,53
Washer designation	TRA-613
Outer Diameter (mm)	20,625
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Only
Limiting speeds(min-1)	22000
Harmonized Tariff Code	8482.99.25.40

(Refer.)Washer mass(kg)	0.001
Manufacturer Item Number	NTA-613
Single or Double Direction	Single Direction
Basic static load rating (C0)	14,32 kN
Basic dynamic load rating (C)	6,05 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter