



Bearing No. HM231140/HM231110

e	0.32
d	146,05 mm
D	236,538 mm
T	57,15 mm
B	56,642 mm
C	44,45 mm
a	45,9 mm
Da	217 mm
B_	56.642
Db	224 mm
da	164 mm
Y0	1
db	160 mm
C0	720
D_	236.538
Z_	21
C_	44.45
Y1	1.9
DE_	212.448
SLR	42
D_a	217
DI_	168.897
DA1	23.253
DA2	21.426
CUP	2.93
DA_	22.343
D_b	224
RAr	532.98
SDM_	190.993
KBRG	3161

yobi	HM231140/HM231110
CONE	6.07
ALP21	24
ALP22	0
ALP23	0
BETA_	1
BET21	2
BET23	0
BET22	30
r min.	3,5 mm
LangID	1
Weight	9 Kg
ALPHA_	12
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	1900
outer r	3.3
hidYobi	HM231140/HM231110
GRS rpm	1400
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	146.05x236.538x57.15
SHOG_yobi	HM231140/HM231110
Prod_Type3	TRBSR_ID_A
Width (mm)	57,15
Bearing number	HM231140/HM231110
Bore Diameter (mm)	146,05
Outer Diameter (mm)	236,538
Calculation factor (e)	0,32

(Oil) Lubrication Speed	1900 r/min
Calculation factor (Y0)	1
(Grease) Lubrication Speed	1400 r/min
Basic static load rating (C0)	720 kN
Basic dynamic load rating (C)	455 kN