



Bearing No. 23092-B-K-MB + H3092-HG

d	460 mm
l	234 mm
D	680 mm
B	163 mm
c	60 mm
m	204 kg / Weight
e	0,24
Size (mm)	430x680x163
Width (mm)	163
n <sub>B</sub>	440000 N / Fatigue limit load, radial
C <sub>r</sub>	3650000 N / Dynamic load rating (radial)
n <sub>s</sub>	23,5 mm
d <sub>s</sub>	12,5 mm
D <sub>1</sub>	612,2 mm
D <sub>m</sub>	540 mm
Y <sub>1</sub>	2,84
c <sub>1</sub>	75 mm
Y <sub>2</sub>	4,23
Y <sub>0</sub>	2,78
n <sub>G</sub>	970 1/min / Limiting speed
m <sub>1</sub>	71,8 kg
C <sub>0r</sub>	7650000 N / Static load rating (radial)
Bearing number	23092-B-K-MB + H3092-HG
d <sub>1H</sub>	430 mm
r <sub>min</sub>	6 mm

$r_{a \max}$	5 mm
$d_{a \max}$	509 mm
$D_{a \max}$	657 mm
$B_{a \min}$	17 mm
$d_{b \min}$	478 mm
Bore Diameter (mm)	430
Outer Diameter (mm)	680
- H3092-HG / Adapter sleeve	H3092HG / Adapter sleeve