



Bearing No. 23092-B-K-MB+H3092

|                         |                    |
|-------------------------|--------------------|
| C                       | 163 mm             |
| l                       | 234 mm             |
| n                       | 23,5 mm            |
| d                       | 460 mm             |
| D                       | 680 mm             |
| B                       | 163 mm             |
| D1                      | 612,2 mm           |
| C1                      | 75 mm              |
| d5                      | 12,5 r/min         |
| Dm                      | 540 mm             |
| d1                      | 430 mm             |
| Weight                  | 275,6 Kg           |
| r min.                  | 6 mm               |
| da max                  | 509 mm             |
| db min                  | 478 mm             |
| ba min.                 | 17 mm              |
| Da max.                 | 657 mm             |
| ra max.                 | 5 mm               |
| Size (mm)               | 460x680x163        |
| Width (mm)              | 163                |
| Limiting speed          | 700 r/min          |
| Bearing number          | 23092-B-K-MB+H3092 |
| Reference speed         | 580 r/min          |
| Bore Diameter (mm)      | 460                |
| Outer Diameter (mm)     | 680                |
| Calculation factor (e)  | 0,24               |
| Fatigue load limit (Pu) | 520                |
| Calculation factor (Y0) | 2,78               |
| Calculation factor (Y1) | 2,84               |
| Basic dynamic load      | 3650 kN            |

|                               |         |
|-------------------------------|---------|
| rating (C)                    |         |
| Basic static load rating (C0) | 7650 kN |