



Bearing No. 7008 ACD/P4AH

K	0.5 mm
a	20.2 mm
d	40 mm
D	68 mm
B	15 mm
Ball - z	18
Size (mm)	68x40x15
Width (mm)	15
Mass bearing	0.19 kg
$d_n$	50.8 mm
$D_1$	58.8 mm
$d_1$	49.2 mm
$C_1$	8.95 mm
$D_1$	58.8 mm
$d_2$	49.2 mm
$C_1$	8.95 mm
$d_1$	49.2 mm
$d_n$	50.8 mm
$d_2$	49.2 mm
Bearing number	7008 ACD/P4AH
Preload class B	124 N/micron
Preload class A	96 N/micron
Preload class D	214 N/micron
$G_{ref}$	2.4 cm <sup>3</sup>
Preload class C	162 N/micron
Number of balls z	18
Bore Diameter (mm)	68
$r_b$ max.	0.3 mm
$r_a$ max.	1 mm

$D_b$ max.	66 mm
$D_a$ max.	63.4 mm
$d_a$ min.	44.6 mm
$d_b$ min.	44.6 mm
Outer Diameter (mm)	40
$r_a$ - max.	1 mm
$D_a$ - max.	63.4 mm
$d_b$ - min.	44.6 mm
$d_a$ - min.	44.6 mm
$r_{1,2}$ min.	1 mm
$r_{3,4}$ min.	0.3 mm
Ball - $D_w$	7.938 mm
$r_b$ - max.	0.3 mm
$D_b$ - max.	66 mm
Calculation factor f	1.06
Calculation factor e	0.68
Calculation factor - f	1.06
$r_{1,2}$ - min.	1 mm
$r_{3,4}$ - min.	0.3 mm
Calculation factor - e	0.68
Ball diameter $D_w$	7.938 mm
Basic dynamic load rating C	15.9 kN
Preload class A $G_A$	100 N
Preload class B $G_B$	200 N
Preload class C $G_C$	400 N
Basic dynamic load rating - C	15.9 kN
Preload class D $G_D$	800 N
Preload class B - $G_B$	200 N
Preload class A - $G_A$	100 N
Preload class D - $G_D$	800 N

Preload class C - $G_C$	400 N
Fatigue load limit $P_u$	0.44 kN
Calculation factor $f_1$	0.99
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.02
Calculation factor $f_{2C}$	1.05
Calculation factor $f_{2D}$	1.08
Calculation factor $f_{HC}$	1
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Calculation factor - $f_1$	0.99
Limiting speed for oil lubrication	30000 mm/min
Fatigue load limit - $P_u$	0.44 kN
Calculation factor - $f_{2D}$	1.08
Calculation factor - $f_{HC}$	1
Calculation factor - $f_{2C}$	1.05
Calculation factor - $f_{2B}$	1.02
Calculation factor - $f_{2A}$	1
Limiting speed for grease lubrication	19000 r/min
Basic static load rating $C_0$	10.4 kN
Static axial stiffness, preload class A	96 N/ $\mu$ m
Static axial stiffness, preload class D	214 N/ $\mu$ m
Static axial stiffness, preload class C	162 N/ $\mu$ m
Static axial stiffness,	124 N/ $\mu$ m

preload class B	
Attainable speed for grease lubrication	19000 r/min
Basic static load rating - $C_0$	10.4 kN
Attainable speed for oil-air lubrication	30000 r/min
Reference grease quantity $G_{ref}$	2.4 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67