

**Bearing No. 23172-K-MB + AH3172G-H**

l	229 mm
e	0,33
D	600 mm
B	192 mm
a	9 mm
b	35 mm
m	221 kg / Weight
d	360 mm
Size (mm)	340x600x192
Width (mm)	192
d <sub>s</sub>	12,5 mm
C <sub>r</sub>	3800000 N / Dynamic load rating (radial)
n <sub>s</sub>	23,5 mm
D <sub>1</sub>	520 mm
Y <sub>1</sub>	2,06
Y <sub>2</sub>	3,06
Y <sub>0</sub>	2,01
n <sub>G</sub>	1030 1/min / Limiting speed
n <sub>B</sub>	560 1/min / Reference speed
m <sub>1</sub>	29,8 kg / Weight, withdrawal sleeve
C <sub>0r</sub>	7350000 N / Static load rating (radial)
Bearing number	23172-K-MB + AH3172G-H
d <sub>1H</sub>	340 mm
d <sub>2G</sub>	Tr380X5

$C_{ur}$	355000 N / Fatigue limit load, radial
$r_{min}$	5 mm
$r_{a\ max}$	4 mm
$d_{a\ min}$	380 mm
$D_{a\ max}$	580 mm
Bore Diameter (mm)	340
Outer Diameter (mm)	600
- AH3172G-H / Designation, withdrawal sleeve	AH3172GH / Designation, withdrawal sleeve