



Bearing No. 231/500-B-K-MB+AHX31/500

| | |
|-------------------------------|--------------------------|
| n | 23,5 mm |
| C | 264 mm |
| b | 47 mm |
| a | 12 mm |
| l | 313 mm |
| d | 500 mm |
| D | 830 mm |
| B | 264 mm |
| d5 | 12,5 r/min |
| D1 | 720,9 mm |
| d1 | 480 mm |
| Weight | 627,3 Kg |
| r min. | 7,5 mm |
| da min. | 532 mm |
| Da max. | 798 mm |
| ra max. | 6 mm |
| Size (mm) | 500x830x264 |
| Width (mm) | 264 |
| Thread (G) | Tr550X6 |
| Limiting speed | 600 r/min |
| Bearing number | 231/500-B-K-MB+AHX31/500 |
| Reference speed | 340 r/min |
| Bore Diameter (mm) | 500 |
| Outer Diameter (mm) | 830 |
| Calculation factor (e) | 0,32 |
| Fatigue load limit (Pu) | 990 |
| Calculation factor (Y0) | 2,06 |
| Calculation factor (Y1) | 2,1 |
| Basic dynamic load rating (C) | 7100 kN |

| | |
|----------------------------------|----------|
| Basic static load rating (C0) | 14300 kN |
|----------------------------------|----------|