



Bearing No. KRV 22 PPXA

d	10 mm
D	22 mm
B	36 mm
C	12 mm
G	M 10x1
M	4 mm
SW	5 mm
Category	Bearings
Inventory	0.0
Size (mm)	10x22x36
Width (mm)	36
Hexagonal nut	M 10x1
Product Group	B04144
B ₁	23 mm
C ₁	0.6 mm
d ₁	17.5 mm
G ₁	12 mm
C ₁	0.6 mm
B ₁	23 mm
d ₁	17.5 mm
G ₁	12 mm
Grease fitting	NIP A1x4.5
Bearing number	KRV 22 PPXA
Limiting speed	3600 r/min
Weight / Kilogram	0.053
Mass cam follower	0.045 kg
Manufacturer Name	SKF
Bore Diameter (mm)	10
Outer Diameter (mm)	22

Mass support roller	0.045 kg
$r_{1,2}$ min.	0.3 mm
Minimum Buy Quantity	N/A
$r_{1,2}$ - min.	0.3 mm
Basic dynamic load rating C	6.05 kN
Basic dynamic load rating - C	6 kN
Recommended tightening torque	15 N·m
Fatigue load limit P_u	1.04 kN
Fatigue load limit - P_u	1 kN
Basic static load rating C_0	9.15 kN
Basic static load rating - C_0	9.2 kN
Maximum dynamic radial loads - F_r	5.7 kN
Maximum static radial loads - F_{0r}	8.2 kN
Maximum dynamic radial loads F_r max.	5.7 kN
Maximum static radial loads F_{0r} max.	8.15 kN