



Bearing No. KRV 30 B

G	M 12x1.5
B	40 mm
M	4 mm
C	14 mm
D	30 mm
d	12 mm
SW	6 mm
Category	Bearings
Size (mm)	12x30x40
Inventory	0.0
Width (mm)	40
d_1	23 mm
Product Group	B04120
B_1	25 mm
B_2	6 mm
C_1	0.6 mm
M_1	3 mm
B_1	25 mm
M_1	3 mm
G_1	13 mm
G_1	13 mm
d_1	23 mm
C_1	0.6 mm
B_2	6 mm
Hexagonal nut	M 12x1.5
Grease fitting	NIP A1x4.5
Bearing number	KRV 30 B
Limiting speed	3200 r/min
Mass cam follower	0.089 kg

Manufacturer Name	SKF
Weight / Kilogram	0
Bore Diameter (mm)	12
Mass support roller	0.089 kg
Outer Diameter (mm)	30
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	0.6 mm
$r_{1,2}$ - min.	0.6 mm
Basic dynamic load rating C	8.97 kN
Basic dynamic load rating - C	9 kN
Recommended tightening torque	22 N·m
Fatigue load limit P_u	1.66 kN
Fatigue load limit - P_u	1.7 kN
Basic static load rating C_0	14.6 kN
Basic static load rating - C_0	14.6 kN
Maximum dynamic radial loads - F_r	11 kN
Maximum static radial loads - F_{0r}	15.6 kN
Maximum dynamic radial loads F_r max.	11 kN
Maximum static radial loads F_{0r} max.	15.6 kN