



Bearing No. KRV 40 PPXA

G	M 18x1.5
B	58 mm
M	6 mm
C	20 mm
D	40 mm
d	18 mm
SW	8 mm
Category	Bearings
Size (mm)	18x40x58
Inventory	0.0
Width (mm)	58
d ₁	31.5 mm
Product Group	B04144
B ₁	36.5 mm
B ₂	8 mm
C ₁	0.8 mm
M ₁	3 mm
B ₁	36.5 mm
M ₁	3 mm
G ₁	19 mm
G ₁	19 mm
Hexagonal nut	M 18x1.5
d ₁	31.5 mm
C ₁	0.8 mm
B ₂	8 mm
Bearing number	KRV 40 PPXA
Limiting speed	2200 r/min
Grease fitting	NIP A2x7.5
Weight / Kilogram	0.249

Mass cam follower	0.25 kg
Manufacturer Name	SKF
Bore Diameter (mm)	18
Outer Diameter (mm)	40
Lubrication adapter	AP 8
Mass support roller	0.247 kg
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	1 mm
$r_{1,2}$ - min.	1 mm
Basic dynamic load rating C	14.2 kN
Basic dynamic load rating - C	14.2 kN
Recommended tightening torque	87 N·m
Fatigue load limit P_u	3.1 kN
Fatigue load limit - P_u	3.1 kN
Basic static load rating C_0	26.5 kN
Basic static load rating - C_0	26.5 kN
Maximum dynamic radial loads - F_r	17 kN
Maximum static radial loads - F_{0r}	24.5 kN
Maximum dynamic radial loads F_r max.	17 kN
Maximum static radial loads F_{0r} max.	24.5 kN