



### Bearing No. KRVE 30 PPA

G	M 12x1.5
c	0.5 mm
D	30 mm
d	15 mm
B	40 mm
C	14 mm
M	4 mm
SW	6 mm
Category	Bearings
Size (mm)	15x30x40
Inventory	0.0
Width (mm)	40
B <sub>3</sub>	11 mm
C <sub>1</sub>	0.6 mm
Product Group	B04144
M <sub>1</sub>	3 mm
B <sub>1</sub>	25 mm
B <sub>2</sub>	6 mm
B <sub>3</sub>	11 mm
G <sub>1</sub>	13 mm
d <sub>1</sub>	23 mm
C <sub>1</sub>	0.6 mm
M <sub>1</sub>	3 mm
B <sub>1</sub>	25 mm
G <sub>1</sub>	13 mm
B <sub>2</sub>	6 mm
d <sub>1</sub>	23 mm
Hexagonal nut	M 12x1.5
Bearing number	KRVE 30 PPA

Limiting speed	3200 r/min
Grease fitting	NIP A1x4.5
Manufacturer Name	SKF
Weight / Kilogram	0.111
Mass cam follower	0.096 kg
Bore Diameter (mm)	15
Outer Diameter (mm)	30
Mass support roller	0.096 kg
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	0.6 mm
$r_{1,2}$ - min.	0.6 mm
Basic dynamic load rating C	8.97 kN
Basic dynamic load rating - C	9 kN
Recommended tightening torque	22 N·m
Fatigue load limit $P_u$	1.66 kN
Fatigue load limit - $P_u$	1.7 kN
Basic static load rating $C_0$	14.6 kN
Basic static load rating - $C_0$	14.6 kN
Maximum dynamic radial loads - $F_r$	11 kN
Maximum static radial loads - $F_{0r}$	15.6 kN
Maximum dynamic radial loads $F_r$ max.	11 kN
Maximum static radial loads $F_{0r}$ max.	15.6 kN