



Bearing No. KRVE 62 PPA

c	1 mm
M	8 mm
G	M 24x1.5
D	62 mm
d	28 mm
B	80 mm
C	29 mm
SW	14 mm
UNSPSC	31171530
Category	Bearings
Size (mm)	28x62x80
Inventory	0.0
Width (mm)	80
Product Group	B04144
B ₁	49.5 mm
B ₂	11 mm
B ₃	22 mm
C ₁	0.8 mm
d ₁	44 mm
G ₁	25 mm
M ₁	4 mm
Hexagonal nut	M 24x1.5
d ₁	44 mm
C ₁	0.8 mm
B ₃	22 mm
B ₂	11 mm
B ₁	49.5 mm
G ₁	25 mm
M ₁	4 mm

Bearing number	KRVE 62 PPA
Limiting speed	1700 r/min
Grease fitting	NIP A3x9.5
Manufacturer Name	SKF
Mass cam follower	0.81 kg
Weight / Kilogram	0.911
Bore Diameter (mm)	28
Outer Diameter (mm)	62
Lubrication adapter	AP 14
Mass support roller	0.815 kg
$r_{1,2}$ min.	1 mm
Minimum Buy Quantity	N/A
$r_{1,2}$ - min.	1 mm
Basic dynamic load rating C	31.4 kN
Basic dynamic load rating - C	31.4 kN
Recommended tightening torque	220 N·m
Fatigue load limit P_u	9 kN
Fatigue load limit - P_u	9 kN
Basic static load rating C_0	72 kN
Basic static load rating - C_0	72 kN
Maximum dynamic radial loads - F_r	72 kN
Maximum static radial loads - F_{0r}	102 kN
Maximum dynamic radial loads F_r max.	72 kN
Maximum static radial loads F_{0r} max.	102 kN