



Bearing No. 7009 ACB/HCP4A

D	75 mm
d	45 mm
B	16 mm
a	22.1 mm
Ball - z	25
Size (mm)	75x45x16
Width (mm)	16
Mass bearing	0.25 kg
d _n	57.2 mm
d _n	57.2 mm
D ₂	65.58 mm
d ₁	56.44 mm
d ₂	55.17 mm
D ₂	65.58 mm
d ₂	55.17 mm
d ₁	56.44 mm
Bearing number	7009 ACB/HCP4A
Preload class A	91 N/micron
G _{ref}	2.93 cm ³
Preload class C	175 N/micron
Preload class B	115 N/micron
Number of balls z	25
Bore Diameter (mm)	75
r _b max.	0.6 mm
r _a max.	1 mm
D _b max.	71.8 mm
D _a max.	70.4 mm
d _a min.	49.6 mm
d _b min.	49.6 mm

Outer Diameter (mm)	45
D _b - max.	71.8 mm
d _a - min.	49.6 mm
Calculation factor e	0.68
Calculation factor f	1.05
r _b - max.	0.6 mm
D _a - max.	70.4 mm
r _a - max.	1 mm
r _{3,4} min.	0.6 mm
r _{1,2} min.	1 mm
Ball - D _w	5.556 mm
d _b - min.	49.6 mm
r _{1,2} - min.	1 mm
r _{3,4} - min.	0.6 mm
Calculation factor - e	0.68
Calculation factor - f	1.05
Basic dynamic load rating C	12.1 kN
Ball diameter D _w	5.556 mm
Preload class B G _B	110 N
Preload class C G _C	330 N
Basic dynamic load rating - C	9 kN
Preload class A G _A	54 N
Preload class B - G _B	110 N
Preload class C - G _C	330 N
Preload class A - G _A	54 N
Fatigue load limit P _u	0.285 kN
Calculation factor f ₁	0.99
Calculation factor f _{2C}	1.05
Calculation factor f _{2A}	1
Calculation factor f _{HC}	1.01

Calculation factor f_{2B}	1.02
Limiting speed for oil lubrication	43000 mm/min
Fatigue load limit - P_u	0.285 kN
Calculation factor - f_1	0.99
Calculation factor - Y_2	1.41
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_0	0.76
Calculation factor - f_{HC}	1.01
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.02
Limiting speed for grease lubrication	28000 r/min
Basic static load rating C_0	11.4 kN
Static axial stiffness, preload class B	115 N/ μ m
Static axial stiffness, preload class A	91 N/ μ m
Attainable speed for grease lubrication	28000 r/min
Static axial stiffness, preload class C	175 N/ μ m
Basic static load rating - C_0	6.8 kN
Attainable speed for oil-air lubrication	43000 r/min
Reference grease quantity G_{ref}	2.93 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor	0.38

(single, tandem) Y_0	
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67