



Bearing No. 7009 ACD/HCP4A

D	75 mm
d	45 mm
B	16 mm
a	22.1 mm
Ball - z	17
Size (mm)	75x45x16
Width (mm)	16
Mass bearing	0.2 kg
d <sub>n</sub>	56.2 mm
d <sub>n</sub>	56.2 mm
D <sub>1</sub>	65.8 mm
d <sub>1</sub>	54.2 mm
d <sub>2</sub>	54.2 mm
D <sub>1</sub>	65.8 mm
d <sub>2</sub>	54.2 mm
d <sub>1</sub>	54.2 mm
Bearing number	7009 ACD/HCP4A
Preload class B	192 N/micron
Preload class A	146 N/micron
Preload class D	343 N/micron
Preload class C	254 N/micron
G <sub>ref</sub>	3.3 cm <sup>3</sup>
Number of balls z	17
Bore Diameter (mm)	75
r <sub>b</sub> max.	0.3 mm
r <sub>a</sub> max.	1 mm
D <sub>b</sub> max.	73 mm
D <sub>a</sub> max.	70.4 mm
d <sub>a</sub> min.	49.6 mm

d <sub>b</sub> min.	49.6 mm
Outer Diameter (mm)	45
D <sub>b</sub> - max.	73 mm
d <sub>b</sub> - min.	49.6 mm
Ball - D <sub>w</sub>	9.525 mm
r <sub>1,2</sub> min.	1 mm
r <sub>3,4</sub> min.	0.3 mm
d <sub>a</sub> - min.	49.6 mm
r <sub>a</sub> - max.	1 mm
D <sub>a</sub> - max.	70.4 mm
r <sub>b</sub> - max.	0.3 mm
Calculation factor f	1.09
Calculation factor e	0.68
r <sub>1,2</sub> - min.	1 mm
r <sub>3,4</sub> - min.	0.3 mm
Calculation factor - e	0.68
Calculation factor - f	1.09
Ball diameter D <sub>w</sub>	9.525 mm
Basic dynamic load rating C	27.6 kN
Preload class C G <sub>C</sub>	680 N
Preload class B G <sub>B</sub>	340 N
Preload class A G <sub>A</sub>	170 N
Preload class D G <sub>D</sub>	1360 N
Basic dynamic load rating - C	27.6 kN
Preload class B - G <sub>B</sub>	340 N
Preload class D - G <sub>D</sub>	1360 N
Preload class C - G <sub>C</sub>	680 N
Preload class A - G <sub>A</sub>	170 N
Fatigue load limit P <sub>u</sub>	0.9 kN
Calculation factor f <sub>1</sub>	0.99

Calculation factor $f_{2A}$	1
Calculation factor $f_{2C}$	1.05
Calculation factor $f_{2B}$	1.02
Calculation factor $f_{2D}$	1.08
Calculation factor $f_{HC}$	1.02
Calculation factor - $X_2$	0.67
Calculation factor - $f_1$	0.99
Calculation factor - $Y_1$	0.92
Limiting speed for oil lubrication	32000 mm/min
Calculation factor - $Y_0$	0.76
Fatigue load limit - $P_u$	0.9 kN
Calculation factor - $Y_2$	1.41
Calculation factor - $f_{HC}$	1.02
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2C}$	1.05
Calculation factor - $f_{2B}$	1.02
Calculation factor - $f_{2D}$	1.08
Limiting speed for grease lubrication	20000 r/min
Basic static load rating $C_0$	21.6 kN
Static axial stiffness, preload class B	192 N/ $\mu\text{m}$
Attainable speed for grease lubrication	20000 r/min
Static axial stiffness, preload class D	343 N/ $\mu\text{m}$
Static axial stiffness, preload class C	254 N/ $\mu\text{m}$
Static axial stiffness, preload class A	146 N/ $\mu\text{m}$
Basic static load rating -	21.6 kN

$C_0$	
Attainable speed for oil-air lubrication	32000 r/min
Reference grease quantity $G_{ref}$	3.3 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67