



Bearing No. 7009 ACE/P4A

D	75 mm
d	45 mm
B	16 mm
a	22.2 mm
Ball - z	21
Size (mm)	75x45x16
Width (mm)	16
Mass bearing	0.24 kg
$d_n$	57.6 mm
$d_n$	57.6 mm
$D_1$	64.25 mm
$d_1$	55.7 mm
$d_2$	53.6 mm
$D_1$	64.25 mm
$d_2$	53.6 mm
$d_1$	55.7 mm
Bearing number	7009 ACE/P4A
Preload class A	94 N/micron
$G_{ref}$	3.4 cm <sup>3</sup>
Preload class C	183 N/micron
Preload class B	140 N/micron
Number of balls z	21
Bore Diameter (mm)	75
$r_b$ max.	0.6 mm
$r_a$ max.	1 mm
$D_b$ max.	70.8 mm
$D_a$ max.	70.4 mm
$d_a$ min.	49.6 mm
$d_b$ min.	49.6 mm

Outer Diameter (mm)	45
D <sub>b</sub> - max.	70.8 mm
d <sub>a</sub> - min.	49.6 mm
Calculation factor e	0.68
Calculation factor f	1.06
r <sub>b</sub> - max.	0.6 mm
D <sub>a</sub> - max.	70.4 mm
r <sub>a</sub> - max.	1 mm
r <sub>3,4</sub> min.	0.6 mm
r <sub>1,2</sub> min.	1 mm
Ball - D <sub>w</sub>	7.144 mm
d <sub>b</sub> - min.	49.6 mm
r <sub>1,2</sub> - min.	1 mm
r <sub>3,4</sub> - min.	0.6 mm
Calculation factor - e	0.68
Calculation factor - f	1.06
Basic dynamic load rating C	12.1 kN
Ball diameter D <sub>w</sub>	7.144 mm
Preload class B G <sub>B</sub>	330 N
Preload class C G <sub>C</sub>	660 N
Basic dynamic load rating - C	12.1 kN
Preload class A G <sub>A</sub>	110 N
Preload class B - G <sub>B</sub>	330 N
Preload class C - G <sub>C</sub>	660 N
Preload class A - G <sub>A</sub>	110 N
Fatigue load limit P <sub>u</sub>	0.345 kN
Calculation factor f <sub>1</sub>	0.99
Calculation factor f <sub>2C</sub>	1.06
Calculation factor f <sub>2A</sub>	1
Calculation factor f <sub>HC</sub>	1

Calculation factor $f_{2B}$	1.03
Limiting speed for oil lubrication	37000 mm/min
Fatigue load limit - $P_u$	0.345 kN
Calculation factor - $f_1$	0.99
Calculation factor - $Y_2$	1.41
Calculation factor - $X_2$	0.67
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_0$	0.76
Calculation factor - $f_{HC}$	1
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2C}$	1.06
Calculation factor - $f_{2B}$	1.03
Limiting speed for grease lubrication	24000 r/min
Basic static load rating $C_0$	8.15 kN
Static axial stiffness, preload class B	140 N/ $\mu$ m
Static axial stiffness, preload class A	94 N/ $\mu$ m
Attainable speed for grease lubrication	24000 r/min
Static axial stiffness, preload class C	183 N/ $\mu$ m
Basic static load rating - $C_0$	8.2 kN
Attainable speed for oil-air lubrication	37000 r/min
Reference grease quantity $G_{ref}$	3.4 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor	0.38

(single, tandem) $Y_0$	
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67