



Bearing No. HH932132/HH932110

a	1,8 mm
T	88,9 mm
r	6,3 mm
C	57,15 mm
B	82,55 mm
R	6,3 mm
D	304,8 mm
d	127 mm
Da	288 mm
db	182 mm
da	172 mm
Db	260 mm
Aa	21,5 mm
Ab	8,4 mm
Weight	30,18 Kg
series:	HH932100
Size (mm)	127x304.8x88.9
Width (mm)	88,9
Factor (K)	0,8
cup width:	2.2500 in
Factor (G2)	55,6
Factor (G1)	514,3
cone width:	3.2500 in
Factor (Cg)	0,0381
flange type:	Non-Flanged Cup
closure type:	Open
Bearing number	HH932132/HH932110
bore diameter:	5.0000 in
cage material:	Steel
assembly type:	Cone & Cup

finish/coating:	Uncoated
bearing material:	Chrome Steel
outside diameter:	12.0000 in
Bore Diameter (mm)	127
Outer Diameter (mm)	304,8
static load capacity:	282000 lbf
dynamic load capacity:	260000 lbf, 453000 lbf
Calculation factor (e)	0,73
operating temperature range:	-65 to +250 °F
Basic static load rating (C0)	1250 kN
Basic dynamic load rating (C1)	904 kN
Basic dynamic load rating (C90)	234
Basic dynamic load rating (Ca90)	292