



Bearing No. 7009CDB

| | |
|--------------------|------------------|
| C | 16 mm |
| d | 45 mm |
| B | 16 mm |
| D | 75 mm |
| r1 | 0.6 mm |
| 2B | 32 mm |
| a - | 1.1 mm |
| Width | 16 mm |
| r min. | 1 mm |
| Weight | 0.265 Kg |
| ra max. | 0.6 mm |
| r1 min. | 0.6 mm |
| da min. | 50 mm |
| Da max. | 72 mm |
| ra (max) | 1 mm |
| da1 (min) | 50 mm |
| Bore Size | 45 mm |
| Enclosure | Open |
| Bore Type | Cylindrical Bore |
| ra1 (max) | 0.6 mm |
| Size (mm) | 45x75x16 |
| da2 (min) | 50 mm |
| Da2 (max) | 72 mm |
| Da1 (max) | 70 mm |
| Width (mm) | 16 |
| Configuration | Duplex |
| Bearing number | 7009CDB |
| Angle (?) | 15 ° |
| Outside Diameter | 75 mm |
| Static Load Rating | 39,000 N |
| | |

| | |
|-------------------------------|-------------|
| Bore Diameter (mm) | 45 |
| Dynamic Load Rating | 40,000 N |
| Outer Diameter (mm) | 75 |
| Limiting Speed - Oil | 14,000 rpm |
| Fillet Radius/Chamfer | 1 mm |
| Limiting Speed - Grease | 10,000 rpm |
| (Grease) Lubrication Speed | 10000 r/min |
| Basic dynamic load rating (C) | 40 kN |
| Basic static load rating (C0) | 39 kN |