



**Bearing No. 3187/3120**

|                                  |                      |
|----------------------------------|----------------------|
| C                                | 23,812 mm            |
| R                                | 0,8 mm               |
| d                                | 30,162 mm            |
| D                                | 72,626 mm            |
| T                                | 30,162 mm            |
| B                                | 29,997 mm            |
| r                                | 3,3 mm               |
| Db                               | 61 mm                |
| da                               | 38,5 mm              |
| db                               | 39 mm                |
| Da                               | 67 mm                |
| a -                              | 10,2 mm              |
| Weight                           | 0,6 Kg               |
| Size (mm)                        | 30.162x72.626x30.162 |
| Width (mm)                       | 30,162               |
| Factor (K)                       | 1,76                 |
| Factor (G1)                      | 23,4                 |
| Factor (Cg)                      | 0,0168               |
| Factor (G2)                      | 8,8                  |
| Bearing number                   | 3187/3120            |
| Bore Diameter (mm)               | 30,162               |
| Outer Diameter (mm)              | 72,626               |
| Calculation factor (e)           | 0,33                 |
| Basic static load rating (C0)    | 102 kN               |
| Basic dynamic load rating (C1)   | 87,7 kN              |
| Basic dynamic load rating (C90)  | 22,7                 |
| Basic dynamic load rating (Ca90) | 13                   |

