



Bearing No. GEC 560 TXA-2RS

D	750 mm
d	560 mm
B	258 mm
C	215 mm
?	3 °
?	3 °
Size (mm)	750x560x258
Lubricant	Maintenance free – dry lubrication
Width (mm)	258
d_k	655 mm
d_k	655 mm
Bearing number	GEC 560 TXA-2RS
Sealing solution	Double-lip seals
D_a max.	711 mm
D_a min.	648 mm
d_a max.	602 mm
d_a min.	585 mm
r_2 min.	5 mm
r_1 min.	2 mm
r_a max.	2 mm
r_b max.	5 mm
Mass plain bearing	337 kg
Bore Diameter (mm)	750
Outer Diameter (mm)	560
d_a - min.	585 mm
r_b - max.	5 mm
r_a - max.	2 mm
D_a - max.	711 mm
D_a - min.	648 mm

d _a - max.	602 mm
r ₂ - min.	5 mm
r ₁ - min.	2 mm
Basic dynamic load rating C	38000 kN
Basic dynamic load rating - C	38000 kN
Specific dynamic load factor K	300 N/mm ²
Specific factor dynamic load - K	300 N/mm ²
Basic static load rating C ₀	63000 kN
Basic static load rating - C ₀	63000 kN
Specific static load factor K ₀	500 N/mm ²
Specific factor static load - K ₀	500 N/mm ²
Design (sliding contact surface combination)	Steel/PTFE fabric