



### Bearing No. 6020ZZ

D	150 mm
d	100 mm
B	24 mm
C	24 mm
Bore	3.937 Inch   100 Millimeter
Noun	Bearing
r min.	1,5 mm
da max	112 mm
UNSPSC	31171504
Weight	1,25 Kg
ra max.	1,5 mm
Da max.	142 mm
da min.	108 mm
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Inventory	0.0
Size (mm)	100x150x24
Snap Ring	No
Width (mm)	24
Weight / LBS	2.75578
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Other Features	Deep Groove
Bearing number	6020ZZ
Keyword String	Ball
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>

Outside Diameter	5.906 Inch   150 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Long Description	100MM Bore; 150MM Outside Diameter; 24MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Outer Race Width	0.945 Inch   24 Millimeter
Manufacturer Name	KOYO
Weight / Kilogram	1.362
Internal Clearance	C0-Medium
Bore Diameter (mm)	100
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	4300 r/min
Basic static load rating (C0)	54,2 kN
Basic dynamic load rating (C)	60,2 kN
Maximum Capacity / Filling Slot	No