



### Bearing No. 6020ZZ

D	150 mm
d	100 mm
B	24 mm
C	24 mm
rn	0,5 mm
Bore	3.937 Inch   100 Millimeter
Noun	Bearing
da max	110 mm
UNSPSC	31171504
Weight	1,15 Kg
r min.	1,5 mm
ra max.	1,5 mm
da min.	108 mm
Da max.	142 mm
Category	Single Row Ball Bearing
Size (mm)	100x150x24
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	24
bore type:	Round
Weight / LBS	2.7778
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
bore diameter:	100 mm
Keyword String	Ball
overall width:	24 mm

cage material:	Steel
fillet radius:	1.5 mm
Other Features	Deep Groove   Shell Alvania Prelubricated
Bearing number	6020ZZ
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	100MM Bore; 150MM Outside Diameter; 24MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	0.945 Inch   24 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	5.906 Inch   150 Millimeter
precision rating:	ISO Class 0
outer ring width:	24 mm
inner ring width:	24 mm
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	150 mm
Bore Diameter (mm)	100
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring

Outer Diameter (mm)	150
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	54000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4200 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	60000 N
Internal Special Features	No
(Grease) Lubrication Speed	4 200 r/min
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	54 kN
Basic dynamic load rating (C)	60 kN
Maximum Capacity / Filling Slot	No