



**Bearing No. 6020ZZNR**

D	150,000 mm
C	24,000 mm
B	24,000 mm
d	100,000 mm
Bore	3.937 Inch   100 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	60
Category	Single Row Ball Bearing
Size (mm)	100x150x24
Enclosure	2 Metal Shields
Snap Ring	Yes
Inventory	0.0
Width (mm)	24,000
bore type:	Round
maximum rpm:	5000 RPM
Weight / LBS	2.76
Cage Material	Steel
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Bearing number	6020ZZNR
bore diameter:	100 mm
overall width:	24 mm
fillet radius:	1.5 mm
cage material:	Steel
Keyword String	Ball
Rolling Element	Ball Bearing
finish/coating:	Uncoated

Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	5.906 Inch   150 Millimeter
Long Description	100MM Bore; 150MM Outside Diameter; 24MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Outer Race Width	0.945 Inch   24 Millimeter
Weight / Kilogram	1.303
outer ring width:	24 mm
inner ring width:	24 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	150 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	100,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	150,000
snap ring included:	With Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	54000 N
maximum rpm (grease):	4200 rpm
dynamic load capacity:	60000 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item	6020ZZNR/2A

Number	
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No