



Bearing No. 23136-E1A-K-M + H3136

| | |
|----------------|--------------------------------------------|
| | H3136 / Adapter sleeve |
| m | 25,5 kg / Weight |
| d | 180 mm |
| D | 300 mm |
| B | 96 mm |
| l | 131 mm |
| c | 30 mm |
| e | 0,29 |
| Size (mm) | 160x300x96 |
| Width (mm) | 96 |
| m_1 | 9,67 kg / Weight, adapter sleeve |
| n_B | 1370 1/min / Reference speed |
| C_r | 1420000 N |
| Y_2 | 3,45 |
| Y_0 | 2,26 |
| n_G | 2230 1/min / Limiting speed |
| Y_1 | 2,32 |
| d_s | 8 mm |
| n_s | 15 mm |
| D_m | 230 mm |
| D_1 | 264,8 mm |
| d_{1H} | 160 mm |
| C_{Or} | 1950000 N / Static load rating (radial) |
| Bearing number | 23136-E1A-K-M + H3136 |
| r_{min} | 3 mm |

| | |
|---------------------|--------|
| $r_{a \max}$ | 2,5 mm |
| $d_{b \min}$ | 180 mm |
| $d_{a \max}$ | 204 mm |
| $D_{a \max}$ | 286 mm |
| $B_{a \min}$ | 8 mm |
| Bore Diameter (mm) | 160 |
| Outer Diameter (mm) | 300 |