



Bearing No. 32009JR

D	75 mm
d	45 mm
T	20 mm
B	20 mm
C	15,5 mm
a	16,5 mm
e	0.39
Cr	78.8
Cu	12.6
Y0	0.84
Y1	1.53
C0r	86.5
Bore	1.772 Inch 45 Millimeter
Noun	Bearing
a(mm)	16.5
Da min	67 mm
da max	51 mm
Weight	0,354 Kg
r min.	1 mm
r(min)	1
UNSPSC	31171516
Db(min)	72
db(max)	51
Da(max)	69.5
Da(min)	67
r1(min)	1
Sa(min)	4
Sb(min)	4.5
ra(max)	1

rb(max)	1
da(min)	50.5
ra max.	1 mm
Db min.	72 mm
Da max.	69,5 mm
da min.	50,5 mm
r2 min.	1 mm
rb max.	1 mm
Oil lub.	6600
Category	Tapered Roller Bearings Assembly
Size (mm)	45x75x20
Component	Assembly
Inventory	2.0
Width (mm)	20
Grease lub.	5000
Bearing No.	32009JR
Basic Number	32009
Weight / LBS	0.78
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	0.787 Inch 20 Millimeter
Bearing number	32009JR
Precision Class	Standard
(Refer.)Mass(kg)	0.354
Outside Diameter	2.953 Inch 75 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 45MM Bore; 75MM Outside

	Diameter; 20MM Assembly Width; Single Row of Rollers
Weight / Kilogram	0.35
Manufacturer Name	KOYO
Bore Diameter (mm)	45
Outer Diameter (mm)	75
Minimum Buy Quantity	N/A
Calculation factor (e)	0,39
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	6600 r/min
Calculation factor (Y0)	0,84
Manufacturer Item Number	32009JR
(Grease) Lubrication Speed	5000 r/min
Basic static load rating (C0)	86,5 kN
Basic dynamic load rating (C)	62,8 kN