



Bearing No. 23134-E1-K-TVPB + H3134

|                | H3134 / Adapter sleeve                   |
|----------------|------------------------------------------|
| e              | 0,28                                     |
| D              | 280 mm                                   |
| B              | 88 mm                                    |
| l              | 122 mm                                   |
| c              | 29 mm                                    |
| m              | 19,9 kg / Weight                         |
| d              | 170 mm                                   |
| Size (mm)      | 150x280x88                               |
| Width (mm)     | 88                                       |
| $m_1$          | 8,52 kg                                  |
| $C_r$          | 1220000 N / Dynamic load rating (radial) |
| $n_s$          | 15 mm                                    |
| $d_s$          | 8 mm                                     |
| $n_B$          | 174000 N / Fatigue limit load, radial    |
| $d_2$          | 193,4 mm                                 |
| $D_m$          | 220 mm                                   |
| $D_1$          | 248,1 mm                                 |
| $Y_2$          | 3,53                                     |
| $Y_0$          | 2,32                                     |
| $n_G$          | 2380 1/min / Limiting speed              |
| $Y_1$          | 2,37                                     |
| $C_{0r}$       | 1690000 N / Static load rating (radial)  |
| Bearing number | 23134-E1-K-TVPB + H3134                  |
| $d_{1H}$       | 150 mm                                   |

|                     |        |
|---------------------|--------|
| $r_{min}$           | 2,1 mm |
| $r_{a\ max}$        | 2,1 mm |
| $d_{a\ max}$        | 193 mm |
| $D_{a\ max}$        | 268 mm |
| $B_{a\ min}$        | 8 mm   |
| $d_{b\ min}$        | 180 mm |
| Bore Diameter (mm)  | 150    |
| Outer Diameter (mm) | 280    |