



Bearing No. NKX12T2

d	12 mm
D	21 mm
C	23 mm
Dw	1.5 mm
dw	12 mm
Ca	10.3 kN
Fw	12 mm
D1	26 mm
C1	9 mm
Lw	9.8 mm
C2	6,5 mm
Cr	6 kN
C0r	7.7 kN
Dw1	4.76 mm
C0a	15.4 kN
Mass	0.04 kg
da min	20 mm
rs min	0.3 mm
r min.	0,3 mm
Weight	0,042 Kg
ras max	0.3 mm
ra max.	0,3 mm
da min.	20 mm
Category	Bearings
Inventory	0.0
Nlim (oil)	9,200 rpm
Nlim (grease)	6,400 rpm
Product Group	B04144
Bearing number	NKX12T2
Precision class	P0

Manufacturer Name	NTN
Weight / Kilogram	0.048
Bore Diameter (mm)	12
Outer Diameter (mm)	26
Minimum Buy Quantity	N/A
(Grease) Lubrication Speed	6400 r/min
Static load rating axial (C0)	15,4 kN
Dynamic load rating axial (C)	10,3 kN
Lubrication hole on outer ring	Oui/Yes
Static load rating radial (C0)	7,7 kN
Dynamic load rating radial (C)	6 kN
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C