



Bearing No. 23132 CC/W33

b	13.9 mm
K	7.5 mm
d	160 mm
D	270 mm
B	86 mm
Noun	Bearing
Bore	6.299 Inch 160 Millimeter
Width	3.386 Inch 86 Millimeter
UNSPSC	31171510
series:	231
Category	Spherical Roller Bearing
Size (mm)	270x160x86
Enclosure	Open
Inventory	0.0
bore type:	Straight
Width (mm)	86
cage type:	Inner Ring Guided
maximum rpm:	2400 RPM
Weight / LBS	44.154
Bore Profile	Straight
Mass bearing	20.5 kg
D ₁	234 mm
Cage Material	Steel
closure type:	Open
d ₂	184 mm
Product Group	B04311
Inch - Metric	Metric
fillet radius:	2 mm

cage material:	Steel
overall width:	86 mm
bore diameter:	160 mm
Keyword String	Spherical
Withdrawal Nut	Not Applicable
Relubricatable	Yes
Bearing number	23132 CC/W33
Limiting speed	2400 r/min
finish/coating:	Uncoated
Rolling Element	Spherical Roller Bearing
Mounting Method	Shaft Mount
Reference speed	1900 r/min
outer ring type:	Not Split
Outside Diameter	10.63 Inch 270 Millimeter
Long Description	160MM Straight Bore; 270MM Outside Diameter; 86MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable
Manufacturer URL	http://www.skf.com
Manufacturer Name	SKF
precision rating:	Not Rated
Weight / Kilogram	20.046
bearing material:	Steel
outside diameter:	270 mm
Withdrawal Sleeve	Not Applicable
outer ring width:	86 mm
Bore Diameter (mm)	270
d _a min.	172 mm

D _a max.	258 mm
r _a max.	2 mm
Internal Clearance	C0-Medium
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Outer Diameter (mm)	160
internal clearance:	C0
Minimum Buy Quantity	N/A
r _{1,2} min.	2.1 mm
d _a - min.	172 mm
D _a - max.	258 mm
r _a - max.	2 mm
Calculation factor e	0.3
D ₁ ?	234 mm
d ₂ ?	184 mm
static load capacity:	1370 kN
Calculation factor - e	0.3
dynamic load capacity:	980 kN
r _{1,2} - min.	2.1 mm
lubrication hole type:	Lubrication Groove & Hole
Harmonized Tariff Code	84823080
Number of Rows of Rollers	Double Row
Basic dynamic load rating C	1029 kN
operating temperature range:	Maximum of +390 °F
Basic dynamic load rating - C	1029 kN
Calculation factor Y ₁	2.3
Fatigue load limit P _u	129 kN
Calculation factor Y ₂	3.4
Calculation factor Y ₀	2.2

Calculation factor - Y_1	2.3
Calculation factor - Y_2	3.4
Calculation factor - Y_0	2.2
Fatigue load limit - P_u	129 kN
Basic static load rating C_0	1370 kN
Basic static load rating - C_0	1370 kN