



Bearing No. NUKRE 35 A

G	M 16x1.5
C	18 mm
c	1 mm
M	6 mm
D	35 mm
d	20 mm
B	52 mm
SW	8 mm
Category	Bearings
Inventory	0.0
Size (mm)	20x35x52
Width (mm)	52
B_1	29.5 mm
d_1	27.6 mm
Product Group	B04144
B_1	29.5 mm
B_2	7.8 mm
B_3	12 mm
C_1	3.8 mm
M_1	3 mm
B_2	7.8 mm
G_1	17 mm
M_1	3 mm
G_1	17 mm
Hexagonal nut	M 16x1.5
d_1	27.6 mm
C_1	3.8 mm
B_3	12 mm
Bearing number	NUKRE 35 A

Limiting speed	5000 r/min
Grease fitting	NIP A2x7.5
Mass cam follower	0.18 kg
Manufacturer Name	SKF
Weight / Kilogram	0.217
Bore Diameter (mm)	20
Outer Diameter (mm)	35
Lubrication adapter	AP 8
Mass support roller	0.177 kg
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	0.6 mm
$r_{1,2}$ - min.	0.6 mm
Basic dynamic load rating C	16.8 kN
Basic dynamic load rating - C	16.8 kN
Recommended tightening torque	58 N·m
Fatigue load limit P_u	2 kN
Fatigue load limit - P_u	2 kN
Basic static load rating C_0	17.6 kN
Basic static load rating - C_0	17.6 kN
Maximum dynamic radial loads - F_r	8.6 kN
Maximum static radial loads - F_{0r}	12.2 kN
Maximum dynamic radial loads F_r max.	8.65 kN
Maximum static radial loads F_{0r} max.	12.2 kN