



Bearing No. NUKRE 72 A

G	M 24x1.5
C	28 mm
c	1 mm
M	8 mm
D	72 mm
d	28 mm
B	80 mm
SW	14 mm
Category	Bearings
Inventory	0.0
Size (mm)	28x72x80
Width (mm)	80
B <sub>1</sub>	49.5 mm
d <sub>1</sub>	44 mm
Product Group	B04144
B <sub>1</sub>	49.5 mm
B <sub>2</sub>	11 mm
B <sub>3</sub>	22 mm
C <sub>1</sub>	1.3 mm
M <sub>1</sub>	4 mm
B <sub>2</sub>	11 mm
G <sub>1</sub>	25 mm
M <sub>1</sub>	4 mm
G <sub>1</sub>	25 mm
Hexagonal nut	M 24x1.5
d <sub>1</sub>	44 mm
C <sub>1</sub>	1.3 mm
B <sub>3</sub>	22 mm
Bearing number	NUKRE 72 A

Limiting speed	2000 r/min
Grease fitting	NIP A3x9.5
Mass cam follower	1.05 kg
Manufacturer Name	SKF
Weight / Kilogram	1.117
Bore Diameter (mm)	28
Outer Diameter (mm)	72
Lubrication adapter	AP 14
Mass support roller	1.05 kg
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	1.1 mm
$r_{1,2}$ - min.	1.1 mm
Basic dynamic load rating C	45.7 kN
Basic dynamic load rating - C	45.7 kN
Recommended tightening torque	220 N·m
Fatigue load limit $P_u$	7.1 kN
Fatigue load limit - $P_u$	7.1 kN
Basic static load rating $C_0$	58.5 kN
Basic static load rating - $C_0$	58.5 kN
Maximum dynamic radial loads - $F_r$	34.5 kN
Maximum static radial loads - $F_{0r}$	50 kN
Maximum dynamic radial loads $F_r$ max.	34.5 kN
Maximum static radial loads $F_{0r}$ max.	50 kN