



Bearing No. 6024N

a	3,71 mm
r	2
d	120 mm
D	180 mm
B	28 mm
C	28 mm
b	3,5 mm
fo	15.7
B_	28
ra	2
C0	80
D1	173,66 mm
D_	180
Z_	14
rn	0,5 mm
ro	0.6
DE_	169.05
SRI	9.86
D_a	171
DA_	19.05
SRE	9.86
DI_	130.95
yobi	6024N
mass	2.08
SBRG	10
bomp	0
KBRG	6101
SREX	0.04
SREN	-0.04
SRIN	-0.04

SDM_	150
SRIX	0.04
ALPHA_	0
r min.	2 mm
C_conv	88000
da max	134,5 mm
da min	129
Weight	2,08 Kg
LangID	1
ra max.	2 mm
Da max.	171 mm
Oil rpm	4300
da min.	129 mm
r0 max.	0,6 mm
hidYobi	6024N
GRS rpm	3600
hidTable	ecat_NSRDGB
Size (mm)	120x180x28
Prod_Type3	DGBB_SR_N_OT
Width (mm)	28
Bearing number	6024N
Bore Diameter (mm)	120
Outer Diameter (mm)	180
(Oil) Lubrication Speed	4 300 r/min
(Grease) Lubrication Speed	3 600 r/min
Basic dynamic load rating (C)	88 kN
Basic static load rating (C0)	80 kN