



**Bearing No. 7014DF**

D	110 mm
a	16.0 mm
C	20 mm
B	20 mm
d	70 mm
r1	0.6 mm
2B	40 mm
Width	20 mm
r min.	1.1 mm
Weight	0.660 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	76 mm
Da max.	106 mm
ra (max)	1 mm
da1 (min)	76 mm
Bore Size	70 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	70x110x20
da2 (min)	76 mm
Da2 (max)	106 mm
Da1 (max)	104 mm
Width (mm)	20
Configuration	Duplex
Bearing number	7014DF
Angle (?)	30 °
Outside Diameter	110 mm
Static Load Rating	78,500 N

Bore Diameter (mm)	70
Dynamic Load Rating	69,000 N
Outer Diameter (mm)	110
Limiting Speed - Oil	5,300 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	4,000 rpm
(Grease) Lubrication Speed	4000 r/min
Basic dynamic load rating (C)	69 kN
Basic static load rating (C0)	78,5 kN