



Bearing No. 7015CDB/GNP5

B	40 mm
C	40 mm
d	75 mm
D	115 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Width	1.575 Inch 40 Millimeter
UNSPSC	31171531
series:	70
Preload	Light
Category	Precision Ball Bearings
Inventory	2.0
Size (mm)	75x115x40
Enclosure	Open
Width (mm)	40
duplex type:	Back to Back
Flush Ground	Yes
Weight / LBS	2.732
Inch - Metric	Metric
Cage Material	Nylon
Raceway Style	1 Rib Outer Ring
Product Group	B04270
Contact Angle	15 Degree
closure type:	Open
bore diameter:	75 mm
cage material:	Nylon
overall width:	40 mm
contact angle:	15 °
Keyword String	Angular Contact Ball

fillet radius:	1.1 mm
Bearing number	7015CDB/GNP5
Other Features	Single Row Angular Contact
Precision Class	ABEC 5 ISO P5
Rolling Element	Ball Bearing
Material - Ball	Steel
Angle (?)	15 °
finish/coating:	Uncoated
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	4.528 Inch 115 Millimeter
Long Description	75MM Bore; 115MM Outside Diameter; 40MM Width; Open Enclosure; ABEC 5 ISO P5 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 15 Degree Contact Angle; Nylon Cage Material; 1 Rib Outer Ring Racew
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
inner ring width:	20 mm
precision rating:	ISO Class 5
Weight / Kilogram	1.239
outside diameter:	115 mm
outer ring width:	20 mm
Number of Bearings	2 (1 Pair)
Bore Diameter (mm)	75
maximum rpm (oil):	15760 rpm
Outer Diameter (mm)	115
internal clearance:	C0

Minimum Buy Quantity	N/A
Mounting Arrangement	Duplex-Back to Back
maximum rpm (grease):	9840 rpm
Harmonized Tariff Code	8482.10.50.28
Manufacturer Item Number	7015CDB/GNP5
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
radial static load capacity:	4900 kg
radial dynamic load capacity:	5050 kg