



Bearing No. 32032JR

e	0.46
d	160 mm
D	240 mm
T	51 mm
B	51 mm
C	38 mm
a	52,1 mm
Y0	0.72
Y1	1.31
Db	231 mm
Cu	90.3
Cr	553
C0r	758
Noun	Bearing
Bore	6.299 Inch 160 Millimeter
a(mm)	52.1
da max	175 mm
Da min	213 mm
UNSPSC	31171516
r min.	3 mm
Weight	7,75 Kg
r(min)	3
Db(min)	231
r1(min)	2.5
da(min)	174
db(max)	175
Da(max)	228
Da(min)	213
ra(max)	2.5

Sa(min)	8
r1 min.	2,5 mm
da min.	174 mm
Da max.	228 mm
db max.	175 mm
Db min.	231 mm
ra max.	2,5 mm
r2 min.	2,5 mm
rb(max)	2
rb max.	2 mm
Sb(min)	13
Category	Tapered Roller Bearings Assembly
Oil lub.	1900
Component	Assembly
Inventory	0.0
Size (mm)	160x240x51
Width (mm)	51
Grease lub.	1400
Bearing No.	32032JR
Basic Number	32032
Weight / LBS	17.086
Product Group	B04334
Inch - Metric	Metric
Bearing number	32032JR
Assembly Width	2.008 Inch 51 Millimeter
Keyword String	Tapered
Other Features	High Load Capacity
Precision Class	Standard
(Refer.)Mass(kg)	7.75
Outside Diameter	9.449 Inch 240 Millimeter

Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 160MM Bore; 240MM Outside Diameter; 51MM Assembly Width; Single Row of Rollers
Manufacturer Name	KOYO
Weight / Kilogram	8.77
Bore Diameter (mm)	160
Outer Diameter (mm)	240
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,46
Calculation factor (Y0)	0,72
(Oil) Lubrication Speed	1900 r/min
Flange Outside Diameter	0 Inch 0 Millimeter
Manufacturer Item Number	32032JR
(Grease) Lubrication Speed	1400 r/min
Basic static load rating (C0)	758 kN
Basic dynamic load rating (C)	440 kN