



Bearing No. 32038JR

C	48 mm
d	190 mm
D	290 mm
T	64 mm
B	64 mm
a	62,9 mm
e	0.44
Cr	823
Y0	0.75
Y1	1.36
Cu	131
Db	279 mm
C0r	1170
Bore	7.48 Inch 190 Millimeter
Noun	Bearing
a(mm)	62.9
r(min)	3
UNSPSC	31171516
Weight	14,7 Kg
r min.	3 mm
Da min	257 mm
da max	209 mm
Db min.	279 mm
ra max.	2,5 mm
r1 min.	2,5 mm
r1(min)	2.5
r2 min.	2,5 mm
da(min)	204
da min.	204 mm

db(max)	209
Da(max)	278
Da(min)	257
Db(min)	279
Sa(min)	10
Sb(min)	16
rb(max)	2
Da max.	278 mm
db max.	209 mm
rb max.	2 mm
ra(max)	2.5
Category	Tapered Roller Bearings Assembly
Oil lub.	1500
Inventory	0.0
Component	Assembly
Size (mm)	190x290x64
Width (mm)	64
Bearing No.	32038JR
Grease lub.	1100
Weight / LBS	32.408
Basic Number	32038
Inch - Metric	Metric
Product Group	B04334
Bearing number	32038JR
Assembly Width	2.52 Inch 64 Millimeter
Keyword String	Tapered
Other Features	High Load Capacity
Precision Class	Standard
(Refer.)Mass(kg)	14.7
Manufacturer URL	http://www.koyousa.com
Outside Diameter	11.417 Inch 290 Millimeter

Long Description	Assembly; Standard Precision; 190MM Bore; 290MM Outside Diameter; 64MM Assembly Width; Single Row of Rollers
Manufacturer Name	KOYO
Weight / Kilogram	15.984
Bore Diameter (mm)	190
Outer Diameter (mm)	290
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,44
Calculation factor (Y0)	0,75
(Oil) Lubrication Speed	1500 r/min
Flange Outside Diameter	0 Inch 0 Millimeter
Manufacturer Item Number	32038JR
(Grease) Lubrication Speed	1100 r/min
Basic static load rating (C0)	1170 kN
Basic dynamic load rating (C)	654 kN