



Bearing No. 7016CDF

D	125 mm
a	0.8 mm
C	22 mm
B	22 mm
d	80 mm
r1	0.6 mm
2B	44 mm
Width	22 mm
r min.	1.1 mm
Weight	0.925 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	86 mm
Da max.	121 mm
ra (max)	1 mm
da1 (min)	86 mm
Bore Size	80 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	80x125x22
da2 (min)	86 mm
Da2 (max)	121 mm
Da1 (max)	119 mm
Width (mm)	22
Configuration	Duplex
Bearing number	7016CDF
Angle (?)	15 °
Outside Diameter	125 mm
Static Load Rating	111,000 N

Bore Diameter (mm)	80
Dynamic Load Rating	96,000 N
Outer Diameter (mm)	125
Limiting Speed - Oil	8,800 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	6,200 rpm
(Grease) Lubrication Speed	6200 r/min
Basic dynamic load rating (C)	96 kN
Basic static load rating (C0)	111 kN