



Bearing No. 7019 ACD/HCP4AH1

K	0.5 mm
a	40.1 mm
d	95 mm
D	145 mm
B	24 mm
Ball - z	21
Size (mm)	145x95x24
Width (mm)	24
Mass bearing	1 kg
d <sub>n</sub>	113.7 mm
D <sub>1</sub>	129.6 mm
d <sub>1</sub>	110.4 mm
C <sub>1</sub>	6.41 mm
D <sub>1</sub>	129.6 mm
d <sub>2</sub>	110.4 mm
C <sub>1</sub>	6.41 mm
d <sub>1</sub>	110.4 mm
d <sub>n</sub>	113.7 mm
d <sub>2</sub>	110.4 mm
Bearing number	7019 ACD/HCP4AH1
Preload class B	374 N/micron
Preload class A	286 N/micron
Preload class D	673 N/micron
G <sub>ref</sub>	15.6 cm <sup>3</sup>
Preload class C	497 N/micron
Number of balls z	21
Bore Diameter (mm)	145
r <sub>b</sub> max.	1 mm
r <sub>a</sub> max.	1.5 mm

D <sub>b</sub> max.	141 mm
D <sub>a</sub> max.	138 mm
d <sub>a</sub> min.	102 mm
d <sub>b</sub> min.	102 mm
Outer Diameter (mm)	95
r <sub>a</sub> - max.	1.5 mm
D <sub>a</sub> - max.	138 mm
d <sub>b</sub> - min.	102 mm
d <sub>a</sub> - min.	102 mm
r <sub>1,2</sub> min.	1.5 mm
r <sub>3,4</sub> min.	1 mm
Ball - D <sub>w</sub>	15.875 mm
r <sub>b</sub> - max.	1 mm
D <sub>b</sub> - max.	141 mm
Calculation factor f	1.15
Calculation factor e	0.68
Calculation factor - f	1.15
r <sub>1,2</sub> - min.	1.5 mm
r <sub>3,4</sub> - min.	1 mm
Calculation factor - e	0.68
Ball diameter D <sub>w</sub>	15.875 mm
Basic dynamic load rating C	76.1 kN
Preload class A G <sub>A</sub>	480 N
Preload class B G <sub>B</sub>	960 N
Preload class C G <sub>C</sub>	1920 N
Basic dynamic load rating - C	76.1 kN
Preload class D G <sub>D</sub>	3840 N
Preload class B - G <sub>B</sub>	960 N
Preload class A - G <sub>A</sub>	480 N
Preload class D - G <sub>D</sub>	3840 N

Preload class C - $G_C$	1920 N
Fatigue load limit $P_u$	2.9 kN
Calculation factor $f_1$	0.99
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.02
Calculation factor $f_{2C}$	1.05
Calculation factor $f_{2D}$	1.08
Calculation factor $f_{HC}$	1.02
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Calculation factor - $f_1$	0.99
Limiting speed for oil lubrication	16000 mm/min
Fatigue load limit - $P_u$	2.9 kN
Calculation factor - $f_{2D}$	1.08
Calculation factor - $f_{HC}$	1.02
Calculation factor - $f_{2C}$	1.05
Calculation factor - $f_{2B}$	1.02
Calculation factor - $f_{2A}$	1
Limiting speed for grease lubrication	10000 r/min
Basic static load rating $C_0$	76.5 kN
Static axial stiffness, preload class A	286 N/ $\mu$ m
Static axial stiffness, preload class D	673 N/ $\mu$ m
Static axial stiffness, preload class C	497 N/ $\mu$ m
Static axial stiffness,	374 N/ $\mu$ m

preload class B	
Attainable speed for grease lubrication	10000 r/min
Basic static load rating - $C_0$	76.5 kN
Attainable speed for oil-air lubrication	16000 r/min
Reference grease quantity $G_{ref}$	15.6 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67