



Bearing No. 7019 ACE/HCP4A

D	145 mm
d	95 mm
B	24 mm
a	40.2 mm
Ball - z	26
Size (mm)	145x95x24
Width (mm)	24
Mass bearing	1.08 kg
$d_n$	115.4 mm
$d_n$	115.4 mm
$D_1$	127.61 mm
$d_1$	112.38 mm
$d_2$	109.2 mm
$D_1$	127.61 mm
$d_2$	109.2 mm
$d_1$	112.38 mm
Bearing number	7019 ACE/HCP4A
Preload class A	236 N/micron
$G_{ref}$	17 cm <sup>3</sup>
Preload class C	466 N/micron
Preload class B	354 N/micron
Number of balls z	26
Bore Diameter (mm)	145
$r_b$ max.	1 mm
$r_a$ max.	1.5 mm
$D_b$ max.	139.4 mm
$D_a$ max.	138 mm
$d_a$ min.	102 mm
$d_b$ min.	102 mm

Outer Diameter (mm)	95
D <sub>b</sub> - max.	139.4 mm
d <sub>a</sub> - min.	102 mm
Calculation factor e	0.68
Calculation factor f	1.11
r <sub>b</sub> - max.	1 mm
D <sub>a</sub> - max.	138 mm
r <sub>a</sub> - max.	1.5 mm
r <sub>3,4</sub> min.	1 mm
r <sub>1,2</sub> min.	1.5 mm
Ball - D <sub>w</sub>	12.7 mm
d <sub>b</sub> - min.	102 mm
r <sub>1,2</sub> - min.	1.5 mm
r <sub>3,4</sub> - min.	1 mm
Calculation factor - e	0.68
Calculation factor - f	1.11
Basic dynamic load rating C	41.6 kN
Ball diameter D <sub>w</sub>	12.7 mm
Preload class B G <sub>B</sub>	1130 N
Preload class C G <sub>C</sub>	2270 N
Basic dynamic load rating - C	41.6 kN
Preload class A G <sub>A</sub>	380 N
Preload class B - G <sub>B</sub>	1130 N
Preload class C - G <sub>C</sub>	2270 N
Preload class A - G <sub>A</sub>	380 N
Fatigue load limit P <sub>u</sub>	1.4 kN
Calculation factor f <sub>1</sub>	0.99
Calculation factor f <sub>2C</sub>	1.06
Calculation factor f <sub>2A</sub>	1
Calculation factor f <sub>HC</sub>	1.01

Calculation factor $f_{2B}$	1.03
Limiting speed for oil lubrication	20500 mm/min
Fatigue load limit - $P_u$	1.4 kN
Calculation factor - $f_1$	0.99
Calculation factor - $Y_2$	1.41
Calculation factor - $X_2$	0.67
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_0$	0.76
Calculation factor - $f_{HC}$	1.01
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2C}$	1.06
Calculation factor - $f_{2B}$	1.03
Limiting speed for grease lubrication	13300 r/min
Basic static load rating $C_0$	36 kN
Static axial stiffness, preload class B	354 N/ $\mu$ m
Static axial stiffness, preload class A	236 N/ $\mu$ m
Attainable speed for grease lubrication	13300 r/min
Static axial stiffness, preload class C	466 N/ $\mu$ m
Basic static load rating - $C_0$	36 kN
Attainable speed for oil-air lubrication	20500 r/min
Reference grease quantity $G_{ref}$	17 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor	0.38

(single, tandem) $Y_0$	
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67