



Bearing No. 7019 CB/P4A

D	145 mm
d	95 mm
B	24 mm
a	28.2 mm
Ball - z	26
Size (mm)	145x95x24
Width (mm)	24
Mass bearing	1.3 kg
d_n	115 mm
d_n	115 mm
D_2	130 mm
d_1	113.7 mm
d_2	111.15 mm
D_2	130 mm
d_2	111.15 mm
d_1	113.7 mm
Bearing number	7019 CB/P4A
Preload class A	56 N/micron
Preload class B	74 N/micron
Preload class C	117 N/micron
G_{ref}	14.72 cm ³
Number of balls z	26
D_a max.	138 mm
d_a min.	102 mm
d_b min.	102 mm
D_b max.	140.4 mm
r_a max.	1.5 mm
r_b max.	1 mm
Bore Diameter (mm)	145

Outer Diameter (mm)	95
d_a - min.	102 mm
r_a - max.	1.5 mm
$r_{1,2}$ min.	1.5 mm
Calculation factor f	1.07
D_b - max.	140.4 mm
$r_{3,4}$ min.	1 mm
r_b - max.	1 mm
D_a - max.	138 mm
Ball - D_w	10.319 mm
d_b - min.	102 mm
Calculation factor - f	1.07
$r_{3,4}$ - min.	1 mm
$r_{1,2}$ - min.	1.5 mm
Basic dynamic load rating C	37.7 kN
Ball diameter D_w	10.319 mm
Preload class B G_B	190 N
Preload class A G_A	94 N
Basic dynamic load rating - C	29.6 kN
Preload class C G_C	570 N
Preload class A - G_A	94 N
Preload class C - G_C	570 N
Preload class B - G_B	190 N
Calculation factor f_1	1
Fatigue load limit P_u	1 kN
Calculation factor f_0	9.7
Calculation factor f_{2C}	1.05
Calculation factor f_{2B}	1.02
Calculation factor f_{2A}	1
Calculation factor f_{HC}	1

Calculation factor - f	1
Fatigue load limit - P_u	1 kN
Calculation factor - f_0	9.7
Limiting speed for oil lubrication	18000 mm/min
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	12000 r/min
Basic static load rating C_0	44 kN
Static axial stiffness, preload class A	56 N/ μ m
Static axial stiffness, preload class B	74 N/ μ m
Static axial stiffness, preload class C	117 N/ μ m
Attainable speed for grease lubrication	12000 r/min
Attainable speed for oil-air lubrication	18000 r/min
Basic static load rating - C_0	26 kN
Reference grease quantity G_{ref}	14.72 cm ³