



**Bearing No. 32212-XL**

D	110 mm
d	60 mm
T	29,75 mm
a	24,5 mm
B	28 mm
C	24 mm
Y	1,48
e	0,4
m	1,18 kg / Weight
Size (mm)	60x110x29.75
Width (mm)	29,75
$n_B$	3800 1/min / Reference speed
$n_G$	6600 1/min / Limiting speed
$Y_0$	0,81
$C_r$	158000 N
$d_1$	83,2 mm
$C_{0r}$	171000 N / Static load rating (radial)
$C_{ur}$	26000 N / Fatigue limit load, radial
Bearing number	32212-XL
$D_{b \text{ min}}$	104 mm
$d_{a \text{ max}}$	69 mm
$d_{b \text{ min}}$	69 mm
$r_{a \text{ max}}$	2 mm
$r_{b \text{ max}}$	1,5 mm
$D_{a \text{ min}}$	95 mm
$D_{a \text{ max}}$	101 mm

$C_{b \text{ min}}$	5,5 mm
$C_{a \text{ min}}$	4 mm
Bore Diameter (mm)	60
Outer Diameter (mm)	110
$r_{1, 2 \text{ min}}$	2 mm
$r_{3, 4 \text{ min}}$	1,5 mm