



Bearing No. 32217JR

D	150 mm
d	85 mm
T	38,5 mm
B	36 mm
C	30 mm
a	34,2 mm
e	0.42
Cr	290
Y0	0.79
Y1	1.43
Cu	47.5
C0r	315
Bore	3.346 Inch 85 Millimeter
Noun	Bearing
a(mm)	34.2
Da min	130 mm
da max	96 mm
Weight	2,8 Kg
r min.	2,5 mm
r(min)	2.5
UNSPSC	31171516
Db(min)	142
db(max)	96
Da(max)	140
Da(min)	130
r1(min)	2
Sa(min)	5
Sb(min)	8.5
ra(max)	2

rb(max)	2
da(min)	97
ra max.	2 mm
Db min.	142 mm
Da max.	140 mm
da min.	97 mm
r2 min.	2 mm
rb max.	2 mm
Oil lub.	3400
Category	Tapered Roller Bearings Assembly
Size (mm)	85x150x38.5
Component	Assembly
Inventory	0.0
Width (mm)	38,5
Grease lub.	2500
Bearing No.	32217JR
Basic Number	32217
Weight / LBS	6.173
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	1.516 Inch 38.5 Millimeter
Bearing number	32217JR
Precision Class	Standard
(Refer.)Mass(kg)	2.80
Outside Diameter	5.906 Inch 150 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 85MM Bore; 150MM Outside

	Diameter; 38.5MM Assembly Width; Single Row of Rollers
Weight / Kilogram	3.024
Manufacturer Name	KOYO
Bore Diameter (mm)	85
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Calculation factor (e)	0,42
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	3400 r/min
Calculation factor (Y0)	0,79
Manufacturer Item Number	32217JR
(Grease) Lubrication Speed	2500 r/min
Basic static load rating (C0)	315 kN
Basic dynamic load rating (C)	232 kN