



**Bearing No. E 209 /NS 7CE3**

|                               |                |
|-------------------------------|----------------|
| D                             | 26 mm          |
| d                             | 9 mm           |
| B                             | 8 mm           |
| C                             | 8 mm           |
| a                             | 8 mm           |
| d1                            | 15,1 mm        |
| D1                            | 20,9 mm        |
| Weight                        | 0,018 Kg       |
| Db max                        | 24,2 mm        |
| db min                        | 11,4 mm        |
| Da max.                       | 23,6 mm        |
| da min.                       | 11,4 mm        |
| r4 min.                       | 0,2 mm         |
| r3 min.                       | 0,2 mm         |
| r2 min.                       | 0,3 mm         |
| r1 min.                       | 0,3 mm         |
| rb max.                       | 0,2 mm         |
| ra max.                       | 0,3 mm         |
| Size (mm)                     | 9x26x8         |
| Width (mm)                    | 8              |
| Bearing number                | E 209 /NS 7CE3 |
| Bore Diameter (mm)            | 9              |
| Outer Diameter (mm)           | 26             |
| (Oil) Lubrication Speed       | 110 000 r/min  |
| Fatigue load limit (Pu)       | 0,067          |
| (Grease) Lubrication Speed    | 70 000 r/min   |
| Basic dynamic load rating (C) | 3,97 kN        |
| Basic static load rating (C0) | 1,6 kN         |

