



**Bearing No. 7026**

a	64 mm
d	130 mm
D	200 mm
B	33 mm
C	33 mm
Bore	5.118 Inch   130 Millimeter
Noun	Bearing
Width	1.299 Inch   33 Millimeter
UNSPSC	31171531
Weight	3,73 Kg
r min.	2 mm
r1 min.	1 mm
da min.	140 mm
ra max.	2 mm
weight:	3.570 kg
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	130x200x33
Inventory	0.0
bore type:	Round
Width (mm)	33
Flush Ground	No
maximum rpm:	4400 rpm
Inch - Metric	Metric
Product Group	B00308
closure type:	Open
Contact Angle	30 Degree

Cage Material	Steel
bore diameter:	130 mm
overall width:	33 mm
cage material:	Brass
contact angle:	30 °
Keyword String	Angular Contact
fillet radius:	2 mm
Bearing number	7026
Rolling Element	Ball Bearing
Angle (?)	25 °
Precision Class	ABEC 1   ISO P0
finish/coating:	Uncoated
Outside Diameter	7.874 Inch   200 Millimeter
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 30 Degree; 1 (Single)
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Name	NTN
outside diameter:	200 mm
precision rating:	ISO Class 0
Weight / Kilogram	3.57
bearing material:	High Carbon Chrome Steel
Bore Diameter (mm)	130
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Outer Diameter (mm)	200

snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single-Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	3 300 r/min
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
radial static load capacity:	125000 N
Basic static load rating (C0)	125 kN
Basic dynamic load rating (C)	117 kN
radial dynamic load capacity:	117000 N
Maximum Capacity / Filling Slot	No